







## KERA RANGE KE50UT

TYPE	Undercounter dishwasher
LINE	KERA RANGE
BASKET	500x500
SIZE	585x600x815h

The warewashers of the Kera range combine **technology**, **design** and **excellent performance** with a strong focus on **sustainability**. Equipped with the latest technology as standard, they guarantee perfect washing and impeccable hygiene in every cycle. Thanks to **Integrated Bluetooth and Wi-Fi connectivity**, each model can be fully managed remotely via the **Krupps Remote Control** app and **iKloud** digital platform.

The Kera range is designed to offer you maximum cleanliness with a savings of over 30% on daily energy consumption.

The **KE50UT** three-phase dishwasher from the **Kera** range is a concentrate of technology, design and excellent wareashing performance. The **vertical TFT touchscreen display** makes it easy to manage each step and to choose and customise the most suitable cycle for every need. The **Acquatech System** technology ensures constant temperature, pressure and consumption, while the **self-regulating system** "**Level Control**" keeps the water level in the tank constant. The **working height of 385 mm** allows precise cleaning of plates, glasses and trays with a productivity of up to **40 baskets/hour**.

The **KE50UT** ensures **extraordinary cleanliness** and considerable energy savings, making it the ideal choice for bars, wine shops, restaurants and all establishments looking for **superior performance**.

[H[ C€ **⊕** 

WRAS APPROVED PRODUCT










DISHWASHERS FEATURES	KERA RANGE KE50UT
Dimensions - (mm) L - P - H	585x600x815h
n° baskets/hour - (+55°C)	Max 40
Height glass max	365mm
Ø height plate max	385mm
Trays	GN1/1 - Special basket required
Tank heating element - Tank capacity	2,6kW - 24lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	0,52kW / 0,7Hp
Total power input / Current	5,92kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
ACCESSORI	
Cutlery insert	2
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
OPTIONAL	
UNIKO touch display with IKLOUD Wi-Fi control	-
pompa_di_scarico_installata_4_w	-
kit_doppie_pareti_isolamento_termo_acustico_e_copertura_superiore	-
Reverse osmosis system	•
Inclined basket for wine glasses dim.500x500x170mm	•
Kit 4 Stainless steel feet 50-70mm	•
2 baskets for glasses Ø400mm	•
"SOFT Door" Opening/Closing System	-
Start Cycle "SOFT Start"	-
"DOUBLE Load" double basket support	•
Wi-Fi connection module	
Optional Installabile, Optional not installable	

## KE50UT





WRAS APPROVED PRODUCT

